


Probing Solutions

HFP1000 HFP1500 HFP2500 Active Probes

LEADING SPECIFICATIONS

- 1 GHz to 2.5 GHz Bandwidth
- 0.7 pF Input Capacitance
- ± 8 V Dynamic Range
- ± 12 V Offset Range
- 5 Interchangeable Tips for Probing a Variety of Test Points
- Replaceable Probe Tip Socket
- Hands-Free Probing with FreeHandProbe Holder
- AutoColor-ID Feature Matches the Probe Color to the Trace Color



HFP2500 probe with FreeHand probe holder and accessories.

Engineers are using an ever-increasing variety of devices and test points in their designs. In order to access these test points conveniently, today's probing solutions need to be versatile, small and lightweight, while still maintaining a high bandwidth. LeCroy's new HFP series of probes is designed to meet these challenges.

Convenient Hands-Free Probing


Five different styles of tips make probing easier than ever. In addition to a traditional Straight Tip, a Sharp Tip allows easier access to tightly-packed test points and circuit vias. The Bent Sharp Tip — made out of titanium — is ideal for making contact on devices that are spaced close together and prevent the probe from being oriented perpendicular to the circuit. The IC Lead Tip has insulation on one side so it can be wedged between small-

geometry IC leads without shorting the test points. The Discrete SMD Tip is designed to fit tightly on surface mount capacitors, resistors and other components.

In conjunction with these innovative probe tips is the LeCroy FreeHandprobe holder, which holds the probe on test points. This means several probes can be used at the same time on a variety of test points while maintaining short signal paths to preserve signal fidelity. The end result of "HFP hands-free probing" is the enhanced ability to analyze waveforms instead of focusing your concentration on keeping the probe in place.

In addition to these new attachment techniques, traditional IC clips, wire leads, and square pin adapters are available.

LeCroy




HFP Probe with Discrete SMD Tip on circuit board.

Easy To Use

When the probe is connected to an oscilloscope channel, our new patent-pending AutoColor ID feature automatically illuminates the probe head in that channel's trace color. Thus, users no longer need to manually apply plastic rings or colored tape to determine which channel the probe is connected to.

With the ProBus® interface, the HFP probes become an integral part of the oscilloscope. The probe offset is controlled from the oscilloscope's front panel.




HFP Probe with IC Lead Tip on circuit board.

Use With Other Test Instruments

HFP1000, HFP1500 and HFP2500 probes can be used with LeCroy's WavePro™ series, LC, and Waverunner™ oscilloscopes, with firmware version 8.7.0 or later.

When used in combination with the ADPPS adapter for ProBus and power supply, the HFP1000 can be used on any manufacturer's oscilloscope or other test instrument. However, the AutoColor ID feature will not function with non-LeCroy oscilloscopes.



Hands-free probing.

Electrical Characteristics

Bandwidth (probe only):

HFP1000	1 GHz
HFP1500	1.5 GHz
HFP2500	2.5 GHz

Attenuation: ± 10

Rise Time (probe only):

HFP1000	≤ 350 ps
HFP1500	≤ 233 ps
HFP2500	≤ 140 ps

Input Capacitance: 0.7 pF

DC Input Resistance: 100 k Ω

Input Dynamic Range: ± 8 V

Probe Offset Range:

HFP1000	N/A
HFP1500	± 12 V
HFP2500	± 12 V

Attenuation Accuracy: $\pm 1\%$

Output Zero: < 4 mV, referred to input

Offset Accuracy: $\pm 1\%$, ± 4 mV, referred to input

General Characteristics

Cable Length: 1.3 m

Probe Head Size:
61 mm (L) x 7.3 mm (W) x 13.1 mm (H)

Input Sockets:

Signal and ground sockets compatible with
0.025" (0.635 mm) square pins,
0.036" (0.91 mm) maximum diameter
(for round pins)

Warranty: One Year

Standard Accessories

HFP1000 includes:

- 4 Straight tips
- 4 Sharp Tips
- 1 Square Pin Ground Spring
- 1 Short Single Lead
- 1 Long Single Lead
- 1 Right-Angle Short Single Lead
- 1 Right-Angle Long Single Lead
- 2 Clips (0.8 mm)
- 1 Replacement Cartridge
- Instruction Manual
- Certificate of Calibration

HFP1500 includes:

- 4 Straight Tips
- 4 Sharp Tips
- 4 Bent Sharp Tips
- 4 SMD Discrete Tips
- 4 IC Lead Tips
- 1 Square Pin Ground Spring
- 1 Ground Spring with Hook
- 2 Short Single Leads
- 2 Long Single Leads
- 2 Right-Angle Short Single Leads
- 2 Right-Angle Long Single Leads
- 2 Clips (0.8 mm)
- 1 FreeHand Probe Holder
- 1 Replaceable Cartridge
- 1 Soft Accessory Case
- Instruction Manual
- Certificate of Calibration

HFP2500 includes:

- all HFP1500 Standard Accessories, and
- 2 Micro Clips (0.5 mm)
- 1 Low C Tip Cartridge

Ordering Information

1 GHz Active Voltage Probe	HFP1000
1.5 GHz Active Voltage Probe	HFP1500
2.5 GHz Active Voltage Probe	HFP2500
Straight Tip	PACC-PT001
Sharp Tip	PACC-PT002
IC Lead Tip	PACC-PT003
SMD Discrete Tip	PACC-PT004
Bent Sharp Tip	PACC-PT005
<i>FreeHand</i> Probe Holder	PACC-MS001
Replaceable Cartridge	PACC-MS002
Low C Cartridge	PACC-MS003
Short Right-Angle Lead	PACC-LD003
Long Right-Angle Lead	PACC-LD004
Short Single Lead	PACC-LD005
Long Single Lead	PACC-LD006
0.8 mm Clips	PK006-4
Micro Clip	PACC-CL001
Ground Spring Hook	PACC-LD001
Square Pin Ground Spring	PACC-LD002
Soft Accessory Case	SAC-01
HFP1000 Instruction Manual, English	HFP1000-OM-E
HFP1500 Instruction Manual, English	HFP1500-OM-E
HFP2500 Instruction Manual, English	HFP2500-OM-E



Copyright © October 2000

LeCroy, ProBus, and SMART Trigger are registered trademarks of LeCroy Corporation. All rights reserved.

Sales and Service Throughout the World

Corporate Headquarters

700 Chestnut Ridge Road
Chestnut Ridge, NY 10977
USA

<http://www.lecroy.com>

LeCroy Sales Offices:

Asia: Hong Kong
Phone (852) 2834 5630
Fax (852) 2834 9893

Austria: Markersdorf
Phone (43) 2749 30050
Fax (43) 2749 30051

Benelux: The Netherlands
Phone (31) 40 211 6998
Fax (31) 40 211 6999

France: Les Ulis
Phone (33) 1 69 18 83 20
Fax (33) 1 69 07 40 42

Germany: Heidelberg
Phone (49) 6221 827 00
Fax (49) 6221 834 655

Italy: Venice
Phone (39) 41 456 97 00
Fax (39) 41 456 95 42

Japan: Osaka
Phone (81) 6 6396 0961
Fax (81) 6 6396 0962

Japan: Tokyo
Phone (81) 3 3376 9400
Fax (81) 3 3376 9587

Japan: Tsukuba
Phone (81) 298 56 0961
Fax (81) 298 56 0962

Korea: Seoul
Phone (82) 2 3452 0400
Fax (82) 2 3452 0490

Spain: Madrid
Phone: (34) 91 640 11 34
Fax: (34) 91 640 06 40

Switzerland: Geneva
Phone (41) 22 719 2111
Fax (41) 22 719 2230

U.K.: Abingdon
Phone (44) 1 235 536 973
Fax (44) 1 235 528 796

U.S.A.: Chestnut Ridge
Phone (1) 845 578 6020
Fax (1) 845 578 5985